



* Excludes consumable battery pack

Technical Data TE 6-A

Power input

375 W

Voltage

36 V

Weight of machine including BP 6-86 battery

10.4 lb

Dimensions (LxWxH)

13" x 3.9" x 8.9"

Battery capacity

BP 6-86: 86 Wh (36 V x 2.4 Ah)

No-load speed

0-890 rpm

Hammering speed


0-5000 blows/min

Single impact energy

1.1 ft-lb

Dust-tight encapsulation and permanent lubrication

Drilling Range



www.us.hilti.com
for Hilti product information

Drill Bits see page:

2.25

KWIK-CON Masonry Screw System see page:

7.41

The Hilti TE 6-A Cordless Rotary Hammer Drill

An Innovative Drilling System for Complete Mobility
With Unmatched Power Reserves



TE-C (SDS)



Advantages


- 36 Volt battery with deep discharge prevention
- Electronic switch for variable speed regulation
- Selector switch to change from hammer drilling to rotary only drilling
- Forward/reverse switch with transport lock
- Exceptional number of holes produced in concrete per charge
- Removable TE-C+ (SDS+) chuck allows quick change to keyed, keyless, or TE-AC angle chuck
- Padded side handle that rotates 360° for added operator comfort
- Ergonomically designed grip

Accessory Program

- Optional belt adapter for overhead use
- TCU 7/36 Universal Charger
- High performance carbide tipped TE-C drill bits from 3/16" to 5/8" diameter
- KWIK-CON driver and KWIK-CON drill bits for rapid installation and removal of KWIK-CON masonry anchor system
- Keyed and keyless chucks

Ordering Information


Item No.	Description
00332013	TE 6-A Standard Equipped with TE-C+ (SDS+) chuck, side handle, dust shield, cleaning cloth, operating instructions and safety precautions. Packed in an impact resistant Hilti case.
00334951	TE 6-A Deluxe Equipped with TE-C+ (SDS+) chuck, side handle, dust shield, cleaning cloth, BP 6-86 battery, TCU 7/36 universal charger, operating instructions and safety precautions. Packed in an impact resistant Hilti case.
00334952	TE 6-A Contractor Equipped with TE-C+ (SDS+) chuck, side handle, dust shield, cleaning cloth, two (2) BP 6-86 batteries, TCU 7/36 universal charger, operating instructions and safety precautions. Packed in an impact resistant Hilti case.
00334953	TE 6-A Utility Equipped with TE-C+ (SDS+) chuck, side handle, dust shield, cleaning cloth, two (2) BP 6-86 batteries, TCU 7/36 universal charger, 1/2" quick release keyed chuck, operating instructions and safety precautions. Packed in an impact resistant Hilti case.



TE 6-A Accessories

Item No.	Description
00333969	BP 6-86 Battery
00333848	TE 6-A BAP Belt Adapter

For attaching the battery to a waist belt. Reduces the working weight of the machine to 6.2 lb, making it ideal for repetitive drilling, particularly when working overhead.



Battery Charger & Adapter

TCU 7/36 Universal Power Charger

Item No.	Description
00337011	TCU 7/36 Universal Power Charger

For all current Hilti battery types (Hilti batteries BP6-86, BP72, BP60, BP40, SBP10 and SBP12). With conditioning charge mode for refreshing.

00335475	Adapter TCU 7/36 CA
----------	---------------------

To charge batteries BP 40, BP 60 and BP 72 on TCU 7/36 Universal Charger



Technical Data BP 6-86 Battery

Voltage

36 V

Battery capacity

36 V x 2.4 Ah = 86 Wh

Weight

4.6 lb

Deep discharge prevention

Right of technical changes reserved

Hilti Battery	Approximate Charging Time
BP-6-86	32 min
BP 40	20 min
BP 60	25 min
BP 72	30 min
RB 10	15 min
SBP 10	15 min
SBP 12	15 min
SFB 105	35 min
SFB 120	35 min